

Slate Polo

OG143

Product Features:

- 8.7 oz/ly (CA), 5.2 oz/sq yd (US), 176 gsm (EU)
- 90/10 performance polyester/spandex with stay-cool wicking technology

Adult sizes: XS-4XL



OGIO woven tab at centre back collar





Available Colours and PMS Colours

Textile fabric colours are subject to dye lot variation and will not be exact match to print Pantone reference.



BLACKTOP
Black C



GEAR GREY
425C



NAVY
533C

Due to the nature of polyester, special care must be taken throughout the decoration process.
OGIO® products may not be resold without embellishment. OGIO® products are not permitted to be shipped to or sold outside of Canada.

OG143 - OGIO® Slate Polo

Garment Measurements

Size	XS	S	M	L	XL	2XL	3XL	4XL
Chest - Half Measure	18"	19 1/2"	21"	22 1/2"	24"	26"	27 1/2"	29 1/2"
Chest - Full Measure	36"	39"	42"	45"	48"	52"	55"	59"
Body Length from HPS	27 1/2"	28 1/2"	29 1/2"	30 1/2"	31 1/2"	32"	33"	33 1/2"
Sleeve Length - CB	16 3/4"	17 1/2"	18 1/4"	19"	19 3/4"	20 1/2"	21 1/4"	22"

Finished measurements in inches. Refer to “How to Measure” guide for detailed information on measurement instructions.

Printing Instructions for Polyester Spandex Blend Fabrics

Due to the nature of polyester/spandex, special care must be taken throughout the decoration process.

EMBROIDERY

- Performance or poly mesh backing is recommended; it is the best to stabilize light weight soft fabrics.
- For best results on Lycra and Spandex, a Ball Point needle is recommended.

SCREEN PRINTING

- Low-cure poly inks are required. Grey or black bleed blockers may be necessary.
- Given the nature of this fabric, high stretch consumables are required.
- Avoid hot stacking when decorating 100% polyester, blends, and pigment dye fabrics.
- Do not use catch bins to avoid potential ghosting, zebra striping or dye migration.
- Do not package product until completely cool. Cooling stations are recommended.

HEAT TRANSFERS

- Test your application process for success prior to all production runs. Ultra-low cure transfers may be required.
- Heat transfers with low cure adhesive and bleed blockers are required for this product.
- Given the nature of this fabric, high stretch consumables are required.
- Avoid hot stacking when decorating 100% polyester, blends, and pigment dye fabrics.
- Do not package product until completely cool. Cooling stations are recommended.
- For best results when using heat applied consumables to avoid a color or sheen change, it is recommended to use a protective foam application pad.

A test sample run is recommended, especially if you have a large order or if your printer does not specialize in printing on performance fabrics.